



型式 Model	容量(L) 給湯量 L/H	タンク寸法 mm			板厚 mm		d	給気 口 A	凝縮 口 A	給湯 口 A	逃し 口 A	排水 口 A	返湯 口 A	給水 口 A	加熱コイル		タンク 重量 kg
		D	H1	H2	胴板 t1	鏡板 t2									管径 Φmm	全長 m	
SVS-5	500	700	1400	2050	3	3	250	50	25	50	25	40	32	40	32	5.5	220
SVS-8	800	800	1500	2200	3	4	250	65	32	65	25	40	40	50	32	8.9	250
SVS-10	1000	900	1450	2200	4	4	300	65	32	65	32	40	40	50	32	11.1	300
SVS-15	1500	1000	1800	2550	4	5	350	80	40	80	32	50	40	65	32	16.6	380
SVS-20	2000	1100	2000	2800	4	5	350	80	40	80	32	50	40	65	32	22.1	500
SVS-25	2500	1200	2100	2950	5	6	350	100	40	100	40	65	50	65	32	27.7	600
SVS-30	3000	1200	2500	3300	5	6	350	100	40	100	40	65	50	80	32	33.2	650
SVS-35	3500	1300	2500	3350	5	6	400	100	40	100	40	65	50	80	32	38.7	700
SVS-40	4000	1400	2500	3400	5	6	400	100	50	100	40	80	50	80	32	44.3	1000
SVS-45	4500	1400	2700	3600	5	6	400	100	50	100	40	80	50	80	32	49.8	1100
SVS-50	5000	1500	2700	3650	6	8	400	100	50	125	40	80	65	100	32	55.3	1200
SVS-55	5500	1600	2700	3700	6	8	400	125	65	125	40	100	65	100	32	60.9	1300
SVS-60	6000	1600	2800	3800	6	8	450	125	65	125	40	100	65	100	32	66.4	1400
SVS-70	7000	1700	2800	3850	6	8	450	125	65	125	50	100	80	125	32	77.5	1550
SVS-80	8000	1800	3000	4100	6	8	450	125	65	125	50	100	80	125	32	88.5	1900
SVS-90	9000	1800	3400	4500	6	8	450	125	65	125	50	100	80	125	32	99.6	2000
SVS-100	10000	2000	2900	4200	8	10	500	150	80	150	65	125	100	150	32	110.7	2200